

PRODUCT DATASHEET**75VA CHASSIS MOUNTED TRANSFORMER**

Designed, manufactured and tested in accordance with;

BS3535, EN60742*, EN61558*, EN60950

CE Marked

Single 230V or Dual 115V primaries

Comprehensive choice of secondary voltages

Flame retardant bobbins and shrouds

Fully shrouded construction

Weight	1.48	Kg
Typical Regulation	8	%
Frequency	50/60	Hz
Max Ambient	25	°C
Bobbin Material	UL94-V0 Class "B" 130°C	

* requires additional over-current / over-temperature protection.

Please see sheet 2 for part numbers.

Dagnall Electronics Ltd
Tel : +44 (0)117 230 2240
sales@dagnall.co.uk
www.dagnall.co.uk

TRX Electronics Ltd
Tel : (00356)21 663011
info@trxelectronics.com
www.trxelectronics.com

Part Numbers

Part No	Primary	Secondary	Recommended Secondary Fuse
D3056	230V	6+6V	6.3AT
D3057	230V	9+9V	4AT
D3058	230V	12+12V	3.15AT
D3059	230V	15+15V	2.5AT
D3060	230V	50+50V	0.8AT
D3061	115+115V	6+6V	6.3AT
D3062	115+115V	9+9V	4AT
D3063	115+115V	12+12V	3.15AT
D3064	115+115V	15+15V	2.5AT
D3065	115+115V	50+50V	0.8AT

Please see sheets 3 for dimensions and pin outs.

PRODUCT DATASHEET

75VA CHASSIS MOUNTED TRANSFORMER

Outline Drawing

